

Vante® TPE SEALER SYSTEM

MECHANICAL SPECIFICATIONS

	4160	4161	4162
Dimensions (W x L x H)	9 x 16.5 x 6 inches 22.5 x 41 x 15 cm	3 x 12.5 x 2 inches 7.5 x 31.5 x 5 cm	3 x 13 x 2 inches 7.5 x 32.5 x 5 cm
Operating Weight	14 lbs (5.4 kg)	2.5 lbs (1.13 kg)	2.6 lbs (1.18 kg)

ELECTRICAL SPECIFICATIONS

Certifications	cTUVus, CE, WEEE, RoHS	—	—
Power Input	100VAC +/-10%, 50-60Hz 115VAC +/-10%, 50-60 Hz 230VAC +/- 10%, 50-60 Hz	100VAC +/-10%, 50-60Hz 115VAC +/-10%, 50-60 Hz 230VAC +/- 10%, 50-60 Hz	100VAC +/-10%, 50-60Hz 115VAC +/-10%, 50-60 Hz 230VAC +/- 10%, 50-60 Hz
Main Fuses	(100VAC units) 4A (115VAC units) 4A (230VAC units) 2A	—	—

PERFORMANCE FACTORS

Tubing Sizes (O.D.)	—	.250 - .688 inches .062 & .094 inch wall thickness	.375 - 1.00 inches .125 inch wall thickness
---------------------	---	---	--

OPERATING CONDITIONS

Temperature	59° -95° F (15° - 35°C)	59° -95° F (15° - 35°C)	59° -95° F (15° - 35°C)
Humidity	70% maximum relative humidity (non-condensing)	70% maximum relative humidity (non-condensing)	70% maximum relative humidity (non-condensing)
Compressed Air Supply	Not Required	—	—